

CONTACT:

HMI
4795 Shepherdsville Road
Louisville, KY 40218
Tel: 502-969-4059
Fax: 800-313-4195
hmiglass.com

DESCRIPTION:

HMI Clear glass is a neutral, distortion-free glass for a wide range of flat glass applications. Available in 1/8" (3mm)*, 3/16 (5mm), 1/4" (6mm), 5/16" (8mm), 3/8" (10mm) & 1/2" (12mm).

APPLICATION:

Interior & Exterior

COMPOSITION:

Clear glass is a soda-lime float glass product with a slightly green inherent color and a darker green edge color that deepens as thickness and length increase.

APPROXIMATE DIMENSIONS:

Cut-to-size; maximum size depends on fabrication facility
Sheet Sizes = 96" x 130"

WEIGHT:

- 5 mm = 2.5 lbs per square foot
- 6 mm = 3 lbs per square foot
- 8 mm = 4 lbs per square foot
- 10 mm = 5 lbs per square foot
- 12 mm = 6.4 lbs per square foot

GLASS PERFORMANCE:

Visible Light Transmittance (VLT) = 88% @ 3/8" (10mm) thickness

SAFETY OPTIONS:

Tempered (SGCC CERTIFIED)

MAINTENANCE:

Warm water with a mild detergent and lint-free is recommended. Abrasives should be avoided. Do not scrape the glass with razors or other metal tools.

RECOMMENDATION:

Glass is porous and is susceptible to staining from minerals in hard water. HMI recommends protecting glass with C.10 Glass Protectant powered by EnduroShield®.

TESTING/CODE COMPLIANCE:

HMI tempered safety glass meets the requirements for ANSI Z97.1 & the CPSC 16FR, Part 1201 (Consumer Product Safety Commission and is SGCC Certified (Safety Glazing Certification Council).



EDGE COLOR GUIDE

LOW IRON GLASS		REGULAR CLEAR GLASS
	Length 12"	
	Length 20"	
	Length 40"	
	Length 60"	
	Length 100"	
	Length 130"	

**Available only in Boston*